



Phone 403-362-0211  
 Fax 403-362-0219  
 Cell 403-501-9397

### SPRING TYPE AXLE ORDER FORM

620 1st Ave E Brooks AB

<b>Consignee:</b>		<b>Date:</b>	
			<b>Purchase Order:</b>
<b>Ship To:</b>		<b>Purchaser:</b>	
		<b>Ship Via:</b>	
		<b>Phone Number:</b>	
		<b>Fax Number:</b>	

Number of Axles Required	<input type="text"/>	Capacity per Axle Required	<input type="text"/>	Hub Face
Type of Spindle Required	Straight <input type="checkbox"/> 4" Drop <input type="checkbox"/>			Spring Center
Brakes Required	Electric <input type="checkbox"/> Hydraulic <input type="checkbox"/> Disc <input type="checkbox"/> None <input type="checkbox"/>			Flange Face-#4
Hubs/Hub-Drums Required	Yes <input type="checkbox"/> No <input type="checkbox"/> Number Of Studs _____			Wheel Size
Springs Required	Yes <input type="checkbox"/> No <input type="checkbox"/>			
Spring Location	Overslung <input type="checkbox"/> Underslung <input type="checkbox"/>			
Hanger Kit Required	Single <input type="checkbox"/> Tandem <input type="checkbox"/> Triple <input type="checkbox"/> None <input type="checkbox"/> Other <input type="checkbox"/>			

Special Information

---



---



---

**Information required to order an axle**

- Hub Face - measured from the hub face on one end to the hub face on the other end
- Spring Center - measured from the center of spring seat on one side to the center of spring seat on the other side.
- Spring Location - Overslung - springs mounted on top of axle.  
 - Underslung - springs mounted on the bottom of axle
- #4. If hub face cannot be measured Brake Flange Face can be used -measured from the outside face of the brake flange on one side to the outside face on the other side.

